

CONSUMER FOODSENSE™

Real-Time Detection and Diagnostic Sensors for Food Screening and Inspection



FOODSENSE™ Making Sense of Food

FOODSENSE™ is a pocket detector using HF-QCM nanotechnology sensors designed to detect and identify a wide range of food contaminants in less than 8 seconds. FOODSENSE™ provides food manufacturers, QA, QC personnel and consumer businesses with the latest sample analysis capabilities uniquely developed to address the global problems of food contamination with specific operational requirements such as farm outdoors and manufacturing floor temperatures.

These enhanced capabilities enable to address an expanded range of users required to inspect incoming raw materials, improve the process monitoring and control the food freshness and standardization. FOODSENSE™ enables to detect potential problems before the food is consumed while reducing the dependency and waiting time for external laboratories.

Feature Highlights

- HF-QCM nanotechnology sensors
- Green and safe
- Sample analysis in 8 seconds
- High-throughput sampling per hour
- Self-calibration
- Remote monitoring and support
- Bluetooth® connectivity
- Real-time Cloud synchronization & reporting
- Reduces dependency on external labs


Applications

- Food freshness evaluation
- Food contaminants screening
- Inspection of incoming raw materials
- Final product control
- On-line quality assurance and control
- Quality control standardization
- Improve process monitoring
- Food shelf-life assessment
- Consumer behavior
- Sensory research

HF-QCM Nanotechnology Sensors

The patented High-Frequency Quartz Crystal Microbalance sensors detect and identify a wide range of substances with great accuracy and speed. The HF-QCM sensors are successfully integrated in the FOODSENSE™ with a unique design of a sensor array coated with selective polymers.

The detection and identification of target materials is based on the piezoelectric effect where changes in mass affect the resonating frequency of the HF-QCM sensors by the adsorption of foreign molecules on their selective coatings. The changes in frequency are accurately detected and measured.




Easy-to-Use Operator Interface

Sample analysis and results require minimal interpretation, so operators may concentrate on obtaining a good sample of their food. The FOODSENSE™ onboard processor automatically transmits the data to an Android or iOS application and includes all data logging, including time, date, and sample analysis for each alarm. A complete history of saved data and alarm files can be viewed, analyzed, downloaded and printed at any time.



Select the food category of the product inspected



Get real-time alerts and their locations worldwide

Cloud Synchronization

- Real-time results transmission to a secure Cloud
- Cloud storage
- Cloud back-up
- Real-time data sharing
- Compatibility with Android 4.3 or higher and iOS 7 and higher



Users

- Food manufacturing companies
- Supermarkets and grocery stores
- Government inspectors
- QA and QC personnel
- Food catering companies
- External laboratories
- Hotels & hospitals
- R&D scientists

Date	Time	Location	Result
March 13, 2017	14:09	Location1	Fruit
March 13, 2017	15:09	Location2	Meat
March 13, 2017	16:37	Location1	Fish
March 13, 2017	14:09	Location1	Fruit
March 13, 2017	01:09	Location3	Fish
March 13, 2017	15:09	Location4	Meat
March 13, 2017	20:09	Location2	Fruit
March 13, 2017	02:06	Location2	Dairy
March 13, 2017	23:09	Location4	Fish

Track and record your alerts with Cloud synchronization

Technical Specifications

Technology	High-Frequency Quartz Crystal Microbalance Sensors (HF-QCM) No gas carrier. No radioactive source
Sample Acquisition	Sample acquisition via the detector nozzle supplied with different types of sampling tips
Contaminants Detected	Wide range of chemical contaminants and spoiled food Specific contaminants can be customized upon customer specifications
Sensitivity	Low parts per million (ppm) range
False Alarm	Less than 3%
Warm-Up Time	Less than 10 seconds
Analysis Time	Less than 8 seconds
Operating System	Via Android 4.3 and IOS7
Data Transfer	Bluetooth® Micro USB Port
Alarm Type	Audio and visual, with substance identification
Multi-Language Support	English, French, Spanish, Italian, Portuguese, German, Polish, Russian, Chinese, Korean, Japanese, Arabic and others
Data Storage	Unlimited data logging, including time, date, sample analysis, and system status
Battery	Rechargeable Lithium-Polymer 3.7V 240mAh battery with up to 5 hours of field operations
Weight	50 gr. including battery
Dimensions	(L x W x H): 4.10" x 1.21" x 1.07" (10.40 x 3.08 x 2.71 cm)
Operating Temperature Range	14°F to 131°F (-10°C to + 55°C), less than 95% relative humidity, non-condensing
Carrying Case	Supplied with a carrying case enabling the protection of the detector and associated sampling probes
Certification	CE Mark and EMC Certification ISO 9001:2015 Manufacturing Standards

ADVANCED SENSOR TECHNOLOGIES

Corporate Headquarters

MS Food Safety (An MS Tech Ltd. Division)
1655 North Fort Myer Drive, Suite 700
Arlington, Virginia 22209, USA
T: +1.703.465.5105 F: +1.703.351.5298

Sales

sales@ms-technologies.com

Technical Support

support@ms-technologies.com

www.ms-technologies.com



MS Food Safety (An MS Tech Ltd. Division) has made all reasonable efforts to ensure that the information in this document is accurate and complete, and disclaims any and all warranties for such accuracy and completeness, and is proprietary. This brochure consists of MS Food Safety general capabilities information that does not contain controlled technical data as defined within the Export Administration Regulations (EAR) Part 734.7-11